

NFR-2006 Keelvar WebHook Registration and Orchestration

ID	NFR-2006
Name	Keelvar WebHook Registration and Orchestration
Author	Richard McArthur (richard.mcarthur-ext@syensqo.com)
Approver	Sascha Wenninger (sascha.wenninger-ext@syensqo.com)

Summary

Several single execute processes need to be completed before Keelvar is able to communicate effectively with SAP Cloud Integration Suite, because of the single execution nature of these calls (for registration) they are being considered as technical configuration but doesn't form part of official configuration documents as they are required only by the Syensqo integration build to facilitate integration.

Execution

A single execution of a authenticated webservice hosted by Keelvar outlining the what/where/when of the expected notifications is set out in the below table with sample calls using POSTMAN (screenshots) for clarity. Keelvar has a well documented API's - <https://docs.keelvar.app/webhook-api/docs/apis/> to use an official reference guide to all functionality.

Description and Technical Details

Webhook registration overview

The screenshot displays the Postman interface for a REST client. The workspace is named 'CLOUD FOUNDRY DEV - KEELVAR'. The selected request is a POST method to the endpoint `https://test.keelvar.dev/api/webhooks`. The request body is in raw JSON format, containing the following details:

```
1 {
2   "url": "https://dev-api.syensqo.com/status",
3   "name": "AwardFeed",
4   "description": "All WebHook SCPI DEV",
5   "triggers": [
6     "AWARD_FEED_UPDATED", "JOB_UPDATED", "SOURCING_EVENTS_FEED_UPDATED"
7   ],
8   "signing_alg": "HMAC_SHA256",
9   "signing_key": "tEnAvVNFx4YYTnAimo1ABwtfgNyndEW7yZwh8BZ4BrI="
10 }
```

The response body is also shown in JSON format, indicating a successful registration:

```
1 {
2   "uuid": "e8389c18-4437-45d7-bc8c-8bbe137db54e",
3   "name": "AwardFeed",
4   "description": "All WebHook SCPI DEV",
5   "url": "https://dev-api.syensqo.com/status",
6   "triggers": [
7     "AWARD_FEED_UPDATED",
8     "JOB_UPDATED",
9     "SOURCING_EVENTS_FEED_UPDATED"
10 ],
11   "signing_alg": "HMAC_SHA256",
12   "signing_key": "8086f99f3e831ae648596b119d85c3f997628c147296c8d2d2f1a822348ec621"
13 }
```

Sample Request

```
{
  "url": "https://dev-api.syensqo.com/status",
  "name": "AwardFeed",
  "description": "All WebHook SCPI DEV",
  "triggers": [
    "AWARD_FEED_UPDATED", "JOB_UPDATED", "SOURCING_EVENTS_FEED_UPDATED"
  ],
  "signing_alg": "HMAC_SHA256",
  "signing_key": "tEnAvVNFx4YYTnAimo1ABwtfGNyndEM7yZwh8BZ4BrI="
}
```

Sample Request Breakdown

Elements of the registration URL

JSON Component	Value	Context	Comments
url	https://dev-api.syensqo.com/status	APIM endpoint and entry point into Syensqo Integration Landscape	This endpoint is exposed with no traditional Authentication
name	AwardFeed	Unique identifier in Keelvar	Simple descriptive name for labeling purpose only
description	All WebHook SCPI DEV	More information on the individual webhook	Simple description can be blank
triggers	AWARD_FEED_UPDATED", "JOB_UPDATED", "SOURCING_EVENTS_FEED_UPDATED	Registration of "WHEN" this hook will be triggered in Keelvar	Keelvar triggering events
signing_alg	HMAC_SHA256	signing algorithm	
signing_key	tEnAvVNFx4YYTnAimo1ABwtfGNyndEM7yZwh8BZ4BrI=	Initial "seeding" of signing key this is not the actual signing key	real signing key is returned in the response from Keelvar

Sample Response from Keelvar

```
{
  "uuid": "e8309c18-4437-45d7-bc8c-0bbe137db54e",
  "name": "AwardFeed",
  "description": "All WebHook SCPI DEV",
  "url": "https://dev-api.syensqo.com/status",
  "triggers": [
    "AWARD_FEED_UPDATED",
    "JOB_UPDATED",
    "SOURCING_EVENTS_FEED_UPDATED"
  ],
  "signing_alg": "HMAC_SHA256",
  "signing_key": "0006f99f3e831ae640596b119d85c3f097620c147296c8d2d2f1a022348ec621"
}
```

Sample Response Breakdown

JSON Component	Value	Context	Comments
----------------	-------	---------	----------

uuid	e8309c18-4437-45d7-bc8c-0bbe137db54e	Keelvar UUID of registered webhook	Used for other operations like delete
name	AwardFeed	confirmation	
description	All WebHook SCPI DEV	confirmation	
url	https://dev-api.syensqo.com/status	confirmation	
triggers	"AWARD_FEED_UPDATED", "JOB_UPDATED", "SOURCING_EVENTS_FEED_UPDATED"	trigger confirmation	
signing_alg	HMAC_SHA256	confirmation	
signing_key	0006f99f3e831ae640596b119d85c3f097620c147296c8d2d2f1a022348ec621	actual signing key that will be used moving forward for messages propagated by this webhook	This will be used to decrypt all future inbound webhook traffic to confirm it is legitimate

Final usage of resulting registration

The returned signing key is stored in APIM for verification of future traffic - as this is an open service on the internet this verification step is crucial to secure operation.

View Key Value Map
Transport
Edit


private.keelvar

Entries (1)

Search

Key	Value	Action
keelvar	b926bece5333700a981dd568890c1c76465e939a0f8a5ff1a329908356d3c17c	

Additional services against webhooks

Delete

Note - HTTP Verb (DELETE) and the URL is pathed to the UUID of the webhook

HTTP

CLOUD FOUNDRY DEV - KEELVAR / Delete Webhooks

DELETE

https://test.keelvar.dev/api/webhooks/e8309c18-4437-45d7-bc8c-0bbe137db54e

Docs

Params

Authorization

Headers (8)

Body

Scripts

Tests

Settings

Auth Type

Bearer Token

The authorization header will be automatically generated when you send the request. Learn more about [Bearer Token](#) authorization.

Token

.....

List

Note - HTTP Verb (GET), Results returned are similar to original registration response but WITHOUT the signing key



CLOUD FOUNDRY DEV - KEELVAR / GET Register Webhook

GET



https://test.keelvar.dev/api/webhooks

Docs

Params

Authorization



Headers (8)

Body

Scripts

Tests

Settings

☒ none

☐ form-data

☐ x-www-form-urlencoded

☐ raw

☐ binary

☐ GraphQL

Th

Body

Cookies

Headers (20)

Test Results



{ } JSON



Preview

Visualize



```
1  {
2    "count": 1,
3    "next": null,
4    "previous": null,
5    "results": [
6      {
7        "uuid": "5a455c96-d0ed-4c90-9189-eca74ed00a3f",
8        "name": "AwardFeed",
9        "description": "All WebHook SCPI DEV",
10       "url": "https://test-api.syensqo.com/v1/keelvar/status",
11       "triggers": [
12         "AWARD_FEED_UPDATED",
13         "JOB_UPDATED",
14         "SOURCING_EVENTS_FEED_UPDATED"
15       ],
16       "signing_alg": "HMAC_SHA256"
17     }
18   ]
19 }
```